

Material Safety Data Sheet

CertainTeed

CertainTeed Corporation
P O Box 860
Valley Forge, PA 19482
(215) 341-7000

Date Prepared 11/11/85

fibrous glass
CertainTeed

Product Identification (Label Name) This MSDS applies to the following

Chemical Name N/A

CertainTeed products:

500° Snap*On™ pipe insulation
850° Snap*On™ pipe insulation
Standard Duct Wrap
Universal Blanket
Snap*Wrap Board™
OEM Fabrication Board
High Temperature Blanket
850° Insulation Board
Industrial Insulation Board
Ultra*Duct™
Ultralite™

Ultraliner™
Insulation for Flexible Duct
Metal Building Insulation (MBI)
Metal Building Panel
Transportation Insulation
Ultracoustic™
Industrial Resilient Blanket
Utility Blanket
Wall and Panel Insulation
Industrial Fabrication Board
Insulation for Certaflex

CAS No. N/A

Common Name(s) Fiber Glass Insulation

Fibrous Glass Insulation

1. INGREDIENTS

Chemical Name
(CAS No.)

Common Name

Exposure Limits

%

Fibrous Glass
(CAS - none)

Fiber Glass

OSHA Nuisance Dust PEL
Total Dust: 15 mg/m³
or 50 mppcf
Respirable Dust: 5 mg/m³
or 15 mppcf

75-97

ACGIH Fiber Glass Dust TLV
10 mg/m³

2. PHYSICAL DATA

Boiling Point N/A

% Volatile By Volume N/A

Melt Point ca 1200°F

Vapor Density (Air = 1) N/A

% Solubility (H₂O) Negligible

Specific Gravity 2.5

Vapor Pressure N/A

Appearance Fibers assembled into tubes, blankets, or boards. The products may

Odor Faint resin odor

be faced with kraft, foil or vinyl facings or a combination thereof. Some products may have a coating.

3. FIRE AND EXPLOSION HAZARD DATA

Flash Point & Method N/A
Flammable Limits N/A
Explosive Limits N/A
Extinguishing Media Use that which is applicable to surrounding fire.
Special Fire Fighting Procedures Treat as with residential building materials.

Unusual Fire and Explosion Hazard Facings on these products may burn. Care should be taken to not leave facing exposed and when working close to an open flame.

4. HEALTH EFFECTS

Primary Routes of Entry Inhalation, skin and eye contact.
Carcinogens No IARC No NTP No OSHA No

Acute: Exposure to fibrous glass may cause temporary skin, eye and upper respiratory irritation.
Chronic: None known.
Medical Conditions Which May Be Aggravated: None known.

5. EMERGENCY AND FIRST AID PROCEDURES

Eye Contact: Flush well with running water for at least 15 minutes. Get medical help if irritation persists.

Skin Contact: Cleanse with soap and water. Get medical help if irritation persists.

Upper Respiratory Irritation: Remove from exposure. Get medical help if irritation persists.

6. PHYSICAL HAZARDS

None

7. SPECIAL PROTECTION INFORMATION

Respiratory: Wear a disposable mask designed for nuisance type dusts where sensitivity to dust and airborne particles may cause irritation to the nose or throat.

Eye Protection: Wear eye protection (goggles) when applying materials.

Skin: Insulation may cause temporary skin irritation. Wear long sleeves, gloves and cap when handling and applying material. Wash work clothes separately and rinse washer.

Mech Maint
CEP.
off
13444
Coast
Elec
Grounds

8. REACTIVITY

This is a stable material.

9. STORAGE INFORMATION

No special requirements.

10. SPILL, LEAK, AND DISPOSAL INFORMATION

Avoid spread of fibrous glass dust.

(See Item 7 for personal protection.)

Waste Disposal Method

Scrap material should be disposed of in a sanitary landfill in accordance with federal, state and local regulations.

11. ADDITIONAL COMMENTS

These products contain a cured phenolic binder. The binder and kraft facing in a fire situation may emit toxic fumes and smoke containing carbon dioxide, carbon monoxide and molecular fragments of hydrocarbon particulates, carbon-hydrogen-nitrogen and nitrogen-oxygen compounds. Coated products may also emit hydrogen chloride.

Vinyl facings may thermally decompose at about 260°C (500°F) and release hydrogen chloride. The AWJ jacketing on pipe insulation will begin to thermally decompose at about 175°C-200°C releasing hydrogen chloride and at about 300°C-350°C release hydrogen fluoride. In a fire situation, carbon monoxide, carbon dioxide, and sulfur dioxide may also be formed.